



## TOPLINE UNDERCOUNTER GLASSWASHER RANGE

The **Topline range** of undercounter glasswashers are the high specification, reliable and versatile choice. They guarantee unrivalled accuracy to temperature management and wash results, whilst optimising energy and chemical savings, every cycle.

With easy to use **soft touch controls** and dynamic **interlocking 3 stage filtration system**, Topline is the premium and refined choice for all your warewashing requirements, whether for front or back of house installations.



## WHY CHOOSE TOPLINE?

### FEATURES

---

- Simple soft touch controls
- 
- Choice of 7 wash programs
- 
- Interlocking 3 stage filtration system
- 
- Powerful wash pump with soft start function
- 
- Optimal chemical dosing
- 
- Rinse booster pump
- 

### BENEFITS

---

- Easy to understand and operate
- 
- Offers flexible and specific wash options
- 
- Keeps wash water cleaner and helps prevent blockages in the wash and drain pumps
- 
- Delivers a superior wash without damaging delicate items
- 
- Precise measuring of the chemical products
- 
- Ensures consistent rinse pressure for sparkling results
- 

TOPLINE - THE REFINED, PREMIUM CHOICE



**UG415DUK-1  
GLASSWASHER**



**SPG515UK  
GLASSWASHER**

## TECHNICAL SPECIFICATIONS

Model with integral water softener as standard	UG415DSUK-1	SPG515SUK
Basket size	400x400 mm	500x500 mm
Machine dimensions (WxDxH)	460x600x705 mm	600x600x820 mm
Cycle times	60, 90, 150, 180, 60, 90, 250 secs	60, 90, 150, 180, 60, 90, 250 secs
Maximum baskets per hour	60	60
Basket clearance height	300 mm	307 mm
Wash pump power rating	0.29 kW	0.7 kW
Drain pump	✓	✓
Rinse booster pump	✓	✓
Electronic detergent and rinse aid dispensers	✓	✓
KIWA compliant break tank	✓	✓
Interlocking 3 stage filtration system	✓	✓
Soft start wash pump	✓	✓
Thermostop, guaranteeing rinse temperature	✓	✓
Optional dual heating temperature management function	✓	✓
Optional freshwater and extended rinse cycles	✓	✓
Self cleaning cycle	✓	✓
Compact pressed wash tank	✓	✓
Water consumption per cycle	2.3 L	3.2 L
Electrical specification	230V 1N 50Hz / 13A / 2.9 kW*	230V 1N 50Hz / 30A / 6.8 kW*
		400V 3N 50Hz / 12A / 6.8 kW
		230V 1N 50Hz / 20A / 4.5 kW
		230V 1N 50Hz / 15A / 3.4 kW
		230V 1N 50Hz / 12A / 2.7 kW
Baskets provided	1x glass basket, 1x flat basket (1x WB40G01, 1x WB40G02)	1x glass basket, 1x flat basket (1x WB50G01, 1x WB50G03)

\* Factory default setting