

## ECOLINE HOOD TYPE RANGE

The **Ecoline range** of hood type dishwashers are the robust, reliable and affordable choice. They guarantee unrivalled accuracy to temperature management and wash results, every cycle.

With easy to use **soft touch controls** and dynamic **interlocking 3 stage filtration system**, Ecoline is the smart, economical choice for all your warewashing requirements, whether for commercial or public sector kitchens.







## WHY CHOOSE ECOLINE?

FEATURES		BENEFITS		
-	Simple hood mounted soft touch controls	-	Easy to understand and operate	
-	Choice of 3 wash programs	-	Offers multiple wash options	
-	Interlocking 3 stage filtration system	-	Keeps wash water cleaner and helps prevent blockages in the wash and drain pumps	
-	Powerful wash pump with soft start function	-	Delivers a superior wash without damaging delicate items	
-	Generous useable wash height	-	Enables washing of larger plates and utensils	
-	Rinse booster pump	-	Ensures consistent rinse pressure for sparkling results	







TECHNICAL SPECIFICATIONS	SPH505 DISHWASHER	SPH505S DISHWASHER
Integral water softener with salt management system	x	•
Basket size	500x500 mm	500x500 mm
Machine dimensions (WxDxH)	635x750x1510/2102 mm	635x750x1510/2102 mm
Cycle times	90, 150, 240 secs	90, 150, 240 secs
Maximum baskets per hour	40	40
Basket clearance height	470 mm	470 mm
Wash pump power rating	0.7 kW	0.7 kW
Drain pump	<b>~</b>	<b>✓</b>
Rinse booster pump	<b>~</b>	<b>~</b>
Electronic detergent and rinse aid dispensers	<b>~</b>	<b>✓</b>
KIWA approved break tank	<b>~</b>	<b>✓</b>
Interlocking 3 stage filtration system	<b>~</b>	<b>✓</b>
Soft start wash pump	<b>~</b>	<b>✓</b>
Thermostop, guaranteeing rinse temperature	<b>~</b>	<b>✓</b>
Optional dual heating temperature management function	<b>✓</b>	<b>✓</b>
Optional freshwater and extended rinse cycles	<b>~</b>	<b>~</b>
Self cleaning cycle	<b>∀</b>	<b>✓</b>
Compact 14 L pressed wash tank	<b>~</b>	<b>✓</b>
Water consumption per cycle	2.7 L	2.7 L
Electrical specification	400V 3N 50Hz / 16A / 9.7 kW*	400V 3N 50Hz / 16A / 9.7 kW
	ification 400V 3N 50Hz / 16A / 9.7 kW* 230V 1N 50Hz / 30A / 6.7 kW	230V 1N 50Hz / 30A / 6.7 kW
	230V 1N 50Hz / 16A / 3.7 kW	230V 1N 50Hz / 16A / 3.7 kW
Baskets provided	1x pegged basket, 1x flat basket, 1x cutlery basket (1x PB50D01, 1x PB50G02 1x PH00S02)	1x pegged basket, 1x flat bask 1x cutlery basket (1x PB50D01, 1x PB50G02 1x PH00S02)

<sup>\*</sup> Factory default setting



